



*** repuesto *** SIMATIC DP, módulo de interfaz maestro DP para IM151-7 CPU o IM151-8 PN/DP (ET200S), módulo con interfaz PROFIBUS DP (conector hembra Sub-D de 9 polos) como maestro DP

Interfaces

PROFIBUS DP	
• Velocidad de transferencia, máx.	12 Mbit/s; 9,6 / 19,2 / 45,45 / 93,75 / 187,5 / 500 kbit/s; 1,5 / 3 / 6 / 12 Mbit/s
• Longitud del cable, máx.	100 m; Apantallado

Protocolos

PROFIBUS DP	Sí
-------------	----

Dimensiones

Ancho	35 mm
Altura	119,5 mm
Profundidad	75 mm

Pesos

Peso, aprox.	100 g
--------------	-------

Clasificaciones

	Versión	Clasificación
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Homologaciones / Certificados

General Product Approval

[Manufacturer Declaration](#)



EG-Konf.



[Miscellaneous](#)



UL



RCM

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[FM](#)



For use in hazardous locations

Maritime application

[Miscellaneous](#)



[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Última modificación:

17/7/2025